



Material No.: Code:

**1.2738 40CrMnNiMo8-6-4**

DE - Brand:

**MCMN**

In the DIN EN ISO 4957 the grades 1.2311 (AISI P20), 1.2312 (AISI P20+S) and 1.2738 (AISI P20+Ni) covered by the above mentioned code were amalgamated. The grade 1.2738 contain additional quantities of Ni and no additional quantities of S.

**Chemical composition:**  
(Typical analysis in %)

C	Mn	Cr	Ni	Mo			
0,40	1,50	1,90	1,00	0,20			

**Steel properties:**

Low sulphur plastic mould steel that is usually supplied in a quenched and tempered condition. The additional Ni content improves the through hardenability large dimensions (>400 mm). Good machinability, better polishability compared to 1.2312 (AISI P20+S).

Similar to AISI P20+Ni.

**Applications:**

Large plastic moulds highly stressed in core, hydroforming tools.

**Condition of delivery:**

Quenched and tempered, 280 - 325 HB  
(950 - 1100 N/mm<sup>2</sup> according to DIN EN ISO 18265 Table A.1)

**Physical properties:**

Thermal expansion coefficient

$\frac{10^{-6} \cdot m}{m \cdot K}$	20-100°C	20-200°C	20-300°C	20-400°C
	11,8	12,5	13,1	13,3

Thermal conductivity

$\frac{W}{m \cdot K}$	20°C	350°C
	39,5	39,1

**Heat treatment:**

Soft annealing

Temperature	Cooling	Hardness
710 - 740°C	furnace	max. 235 HB

Stress relief annealing


The recommendation 500 - 550°C is valid for quenched and tempered condition. In the soft annealed condition stress relieving between 600 - 650°C is possible.

Temperature	Cooling	
500 - 550°C	furnace	


Hardening

Temperature	Cooling	Tempering
840 - 870°C	oil or hot bath 180 - 220°C	see tempering diagram


## (1.2738) Thermal Cycle Diagram



## Continuous Cooling Transformation Diagram (CCT)



## Tempering Diagram



Remarks: All technical information is for reference only.